

MOVE IT 25 ACOUSTIC triangle


inlay
050-231421L



Project / Type


Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; triangular design; high quality visual and tactile surface with embossed pattern, black; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools;

Product drawing



General

Luminaire / Track , Mounted

black

Physical

panel only for NODE connector + track 1210 mm

length 1195 mm

width 1035 mm

height 25 mm

6.8 kg

Acoustics

Alpha w (α_w) 1 ¹

SAC (sound absorption class) A ¹

NRC 1.3 ¹

SAA 1.32 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Installation instructions





Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.33	0.57	0.73	0.97	1.27	1.33

Sound absorption coefficient (α_p)

