

# MOVE IT 25 / 45

## ACOUSTIC square grid


inlay  
050-231121L



Project / Type


Notes

Count / Date



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 60% recycled PET; square design; high quality visual and tactile surface with embossed pattern, black; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 / 45 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools;

### Product drawing



**General**

Luminaire / Track , Mounted

black

**Physical**

panel only for NODE connector + track 1210 mm

length 1235 mm

width 1235 mm

height 25 mm

2.2 kg

**Acoustics**

Alpha w ( $\alpha_w$ ) 1 <sup>1</sup>

SAC (sound absorption class) A <sup>1</sup>

NRC 1.3 <sup>1</sup>

SAA 1.32 <sup>1</sup>

<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

### Installation instructions



# MOVE IT 25 / 45

## ACOUSTIC square grid

inlay  
050-231121L



Project / Type

Notes

Count / Date

### Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.73	1.47	1.73	2.2	2.67	2.77

### Sound absorption coefficient ( $\alpha_p$ )

