

SETA 60 CONEX reflector

direct plug / socket

surface / suspended system
058-4029638B



Project / Type


Notes

Count / Date



Luminaire housing made of extruded aluminium profile; extremely slim design (only Ø 60 mm) linear; converter integrated into luminaire housing; for lighting systems; surface black powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); easy installation using ceiling clips (available as an accessory) or with integrated toolless suspension height adjustment on the luminaire; canopy for through wiring (available as an accessory); electrical connection of the luminaires via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; extruded profile for improved thermal management; high gloss reflector with faceted design; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Suspended

black , RAL9005 ¹

dark chrome

IP20

6460 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

Reflector

symmetric

UGR < 19 , ≥65° <1500 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

system 54 W

PC1 220-240V

system 120 lm/W³

1 DALI Addr.

Physical

length 2936 mm

width 60 mm

height 60 mm

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator



SETA 60 CONEX reflector

direct plug / socket

surface / suspended system

058-4029638B



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B13	40
B16	50
B20	62
C10	52
C13	67
C16	85
C20	104

Mounting accessories

LINEAR CONNECTOR

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
mechanical incl. opal cover connector	pure white		058-3013117
mechanical incl. opal cover connector	jet black		058-3013118
mechanical & electrical incl. opal cover connector	pure white		058-3013127
mechanical & electrical incl. opal cover connector	jet black		058-3013128
mechanical incl. opal cover connector	pure white	60-18-7	058-3013217
mechanical incl. opal cover connector	jet black	60-18-7	058-3013218
mechanical & electrical incl. opal cover connector	pure white	37-23-10	058-3013227
mechanical & electrical incl. opal cover connector	jet black	37-23-10	058-3013228



L CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018727
mechanical & electrical	jet black	058-3018728



T CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018827
mechanical & electrical	jet black	058-3018828



X CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018927
mechanical & electrical	jet black	058-3018928



CONEX flex connector

COLOUR	ARTICLE NUMBER(S)
pure white	058-3018627
jet black	058-3018628



[058-4029638B] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

21.11.2024

SETA 60 CONEX reflector

direct plug / socket

surface / suspended system

058-4029638B



Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING SET

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
pure white	75-20-10	058-3014117
jet black	75-20-10	058-3014118



CABLE SUSPENSION

TYPE	COLOUR	ARTICLE NUMBER(S)
	chrome	058-3014210
	black	058-3014218
angular max. 60°	chrome	058-3014310
angular max. 60°	black	058-3014318



CONNECTOR CABLE SUSPENSION

COLOUR	ARTICLE NUMBER(S)
chrome	058-3018110
black	058-3018118



CANOPY

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
DALI-2	pure white	90	005-2600037
DALI-2	jet black	90	005-2600038



Electrical accessories

END CAP POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
	pure white	058-3010217
	jet black	058-3010218
5 × 1.5 mm ²	pure white	058-3010417
5 × 1.5 mm ²	jet black	058-3010418



MIDDLE POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
	pure white	058-3011217
	jet black	058-3011218
5 × 1.5 mm ²	pure white	058-3011317
5 × 1.5 mm ²	jet black	058-3011318



L CONEX POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
5 × 1.5 mm ²	pure white	058-3018737
5 × 1.5 mm ²	jet black	058-3018738



['058-4029638B'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

21.11.2024

SETA 60 CONEX reflector

direct plug / socket

surface / suspended system
058-4029638B



Project / Type

Notes

Count / Date

Electrical accessories

ESSENTIAL SENSOR

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
DALI-2	pure white	90	058-3019117
DALI-2	jet black	90	058-3019118



SENSE SENSOR

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
DALI-2	pure white	90	058-3019217
DALI-2	jet black	90	058-3019218



Optical accessories

END CAP

COLOUR	ARTICLE NUMBER(S)
pure white	058-3010017
jet black	058-3010018



Optical accessories

BLIND CHANNEL standard

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
incl. through wiring	pure white	585-60-60	058-4922037
incl. through wiring	jet black	585-60-60	058-4922038
incl. through wiring	pure white	1185-60-60	058-4924037
incl. through wiring	jet black	1185-60-60	058-4924038
incl. through wiring	pure white	2351-60-60	058-4928037
incl. through wiring	jet black	2351-60-60	058-4928038
incl. through wiring	pure white	2936-60-60	058-4929037
incl. through wiring	jet black	2936-60-60	058-4929038



BLIND CHANNEL CONEX L/T/X

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
incl. through wiring	pure white	585-60-60	058-4932037
incl. through wiring	jet black	585-60-60	058-4932038
incl. through wiring	pure white	1185-60-60	058-4934037
incl. through wiring	jet black	1185-60-60	058-4934038
incl. through wiring	pure white	2351-60-60	058-4938037
incl. through wiring	jet black	2351-60-60	058-4938038
incl. through wiring	pure white	2936-60-60	058-4939037
incl. through wiring	jet black	2936-60-60	058-4939038

