

# MINO 60 mid lumen

suspended

046-42L3018G



Project / Type

Notes

Count / Date



220-240V

X-PERT

UGR  
≤ 19

cd/m²  
≤ 3000

CRI  
≥ 90

X-PERT

### General

Ceiling , Suspended

black , RAL9005 <sup>1</sup>

1060 lm/m

IP20

925 lm

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Optical

Microprismatic

microprismatic

UGR < 19 , ≥65° <3000 cd/m²

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

non DIM

10.3 W

PC1 220-240V

90 lm/W

12 W/m

### Physical

cable 1500 mm

length 880 mm

width 60 mm

height 80 mm

2.85 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

