

MINO 60 high lumen

suspended

046-4234D37G



Project / Type	
Notes	
Count / Date	



220-240V	X-PERT	TUNABLE WHITE	UGR ≤ 22	CRI ≥ 80	1ADDR	X-PERT
----------	--------	---------------	---------------	---------------	-------	--------

General

Ceiling , Suspended
white , RAL9010 ¹
2230 lm/m
IP20
2620 lm

LED

tunable white
2700 K - 6500 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.48
MDER 0.44

Optical

Microprismatic
microprismatic
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Luminaire housing made of extruded aluminium profile; light tight final end caps made of aluminium; no visible screws; angular design; surface white powder coated; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. feed (white); lighting profile (end cover pre-assembled) available in advance for installation; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour: tunable white diodes (2700-6500 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 / DT8 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical


DALI-2 DT8
25.3 W
PC1 220-240V
104 lm/W
1 DALI Addr.
22 W/m

Physical


length 1500 mm
length 1180 mm
width 60 mm
height 80 mm
3.6 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

