

NOBA 60 suspended

MOVE IT 10

030-6920437



Project / Type	
Notes	
Count / Date	



General

Ceiling , Track Suspended
traffic white , RAL 9016 ¹
IP20
869 lm
optical inset 119 lm/W ²

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.53
MDER 0.48

Optical

wide flood
beam angle 67°
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³


Electrical

DALI-2
48 V
fixture 8.1 W
fixture 107 lm/W ⁴
optical inset 7.3 W
PC3
1 DALI Addr.

Physical

diameter 60 mm
height 60 mm
1500 mm


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	826	1.31
2	207	2.63
3	92	3.94
4	52	5.26
5	33	6.57

Product drawing



¹ RAL code
² OPTICAL INSET: incl. consideration of optical losses
³ Value of containing product at full load (undimmed)
⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

