

# NOBA 50 suspended

MOVE IT 10

030-6910437



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Track Suspended
traffic white , RAL 9016 <sup>1</sup>
IP20
747 lm
optical inset 116 lm/W <sup>2</sup>

### LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

### Optical

wide flood
beam angle 67°
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>


### Electrical

DALI-2
48 V
fixture 7.2 W
fixture 104 lm/W <sup>4</sup>
optical inset 6.4 W
PC3
1 DALI Addr.

### Physical

diameter 50 mm
height 50 mm
1500 mm


### Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	710	1.31
2	178	2.63
3	79	3.94
4	44	5.26
5	28	6.57

### Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

