

TARO 32 downlight

MOVE IT 10 round
030-6740434F



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

chrome

IP20

729 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R_{1-15}: 89

MR 0.53

MDER 0.48

Optical

flood

beam angle 34°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

system 9.6 W

PC3

system 76 lm/W²

1 DALI Addr.

Physical

diameter 32 mm

height 60 mm


Cylindrical spotlight in aluminium; surface polished chrome; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 34° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



flood 34°			
h (m)	E0° (lx)	ø (m)	
1	2380	0.61	
2	590	1.21	
3	260	1.82	
4	150	2.42	
5	100	3.03	

Product drawing



¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions

