

TARO 45 downlight

MOVE IT 10 square
030-6710636M



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 24° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track

brushed aluminium

IP20

1040 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Optical

medium

beam angle 24°

Electrical

DALI-2

11.0 W

PC3

95 lm/W


1 DALI Addr.

Physical

diameter 45 mm

height 75 mm


Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	5010	0.43
2	1250	0.86
3	560	1.30
4	310	1.73
5	200	2.16

Product drawing



Installation instructions

