

NOBA 60 adjustable

MOVE IT 10

030-6820537



Project / Type _____


Notes _____

Count / Date _____



Decorative spotlight inset made of aluminium; surface traffic white powder coated; 365° rotatable and 90° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	876	1.31
2	219	2.63
3	97	3.94
4	55	5.26
5	35	6.57

Product drawing



General

Ceiling / Wall , Track _____

tilt max 90° _____

rotation 365° _____

traffic white , RAL 9016 ¹ _____

IP20 _____

922 lm _____

optical inset 126 lm/W² _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

wide flood _____

beam angle 67° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____

48 V _____

fixture 8.1 W _____

optical inset 7.3 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 60 mm _____

height 60 mm _____

¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

Installation instructions

