

TARO 45 downlight

MOVE IT 10 square
030-6710436F



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 36° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track

brushed aluminium

IP20

949 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R_{1-15}: 89

MR 0.53

MDER 0.48

Optical

flood

beam angle 36°

Electrical

DALI-2

11.0 W

PC3

86 lm/W


1 DALI Addr.

Physical

diameter 45 mm


height 75 mm

Light distribution



flood 36°			
h (m)	E0° (lx)	ø (m)	
1	2830	0.65	
2	710	1.29	
3	310	1.94	
4	180	2.59	
5	110	3.23	

Product drawing



Installation instructions

