

TARO 45 wallwasher/floor

MOVE IT 10 round
030-6790536W



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

rotation 360°

brushed aluminium

IP20

813 lm

optical inset 117 lm/W¹

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.61

MDER 0.55

Optical

wallwasher floor

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

48 V

fixture 9.3 W

optical inset 7.0 W

PC3

1 DALI Addr.

Physical

diameter 45 mm


height 75 mm

¹ OPTICAL INSET: incl. consideration of optical losses


² Value of containing product at full load (undimmed)

Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions

