

TARO 45 wallwasher/floor

MOVE IT 10 round
030-6790437W



Project / Type	
Notes	
Count / Date	



General

Ceiling / Wall , Track	
rotation 360°	
traffic white , RAL 9016 ¹	
IP20	
798 lm	
optical inset 115 lm/W ²	

LED

2700 K	
CRI ≥ 90	
L85 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 101 , R _r : 90 , R _{t1-15} : 88	
MR 0.51	
MDER 0.46	

Optical

wallwasher floor	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical


DALI-2	
48 V	
fixture 9.3 W	
optical inset 7.0 W	
PC3	
1 DALI Addr.	

Physical


diameter 45 mm	
height 75 mm	

Cylindrical spotlight in aluminium; surface traffic white powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² OPTICAL INSET: incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

