

# TARO 45 wallwasher/floor

MOVE IT 10 square  
030-6780437W



Project / Type	
Notes	
Count / Date	



## General

Ceiling / Wall , Track	
rotation 360°	
traffic white , RAL 9016 <sup>1</sup>	
IP20	
798 lm	
optical inset 115 lm/W <sup>2</sup>	

## LED

2700 K	
CRI ≥ 90	
L85 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 101 , R <sub>r</sub> : 90 , R <sub>t1-15</sub> : 88	
MR 0.51	
MDER 0.46	

## Optical

wallwasher floor	
PstLM ≤ 1.0 <sup>3</sup>	
SVM ≤ 0.4 <sup>3</sup>	

## Electrical


DALI-2	
48 V	
fixture 9.3 W	
optical inset 7.0 W	
PC3	
1 DALI Addr.	

## Physical


diameter 45 mm	
height 75 mm	

<sup>1</sup> RAL code  
<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



# TARO 45 wallwasher/floor

MOVE IT 10 square  
030-6780437W



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.982	0.954	0.926	0.899	0.873
LSF	1	1	1	1	1

MF

MF

LMF<sup>a</sup>

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF<sup>a</sup>

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Optical accessories

### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	42	007-1965188



## Optical accessories

### OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965880



### SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965980



### WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965780

