

TARO 32 downlight

MOVE IT 10 round
030-6740534S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

chrome _____

IP20 _____

778 lm _____

optical inset 90 lm/W¹ _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

spot _____

beam angle 18° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 9.6 W _____

fixture 81 lm/W³ _____

optical inset 8.7 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 32 mm _____

height 60 mm _____

Cylindrical spotlight in aluminium; surface polished chrome; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



spot 18°			
h (m)	E0° (lx)	ø (m)	
1	5890	0.32	
2	1470	0.63	
3	650	0.95	
4	370	1.27	
5	240	1.58	

Product drawing



Installation instructions



TARO 32 downlight

MOVE IT 10 round
030-6740534S



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Optical accessories

HONEYCOMB LOUVER

COLOUR

jet black

Ø (MM)

30

ARTICLE NUMBER(S)

007-1965168



Optical accessories

OVAL LENS

Ø (MM)

30

ARTICLE NUMBER(S)

007-1965860



SOFT LENS

Ø (MM)

30

ARTICLE NUMBER(S)

007-1965960



WALLWASHER LENS

Ø (MM)

30

ARTICLE NUMBER(S)

007-1965760

