

TILA 16 suspended

MOVE IT 10

030-6610636F



Project / Type	
Notes	
Count / Date	



General

Ceiling , Track Suspended
brushed aluminium
IP20
220 lm
optical inset 83 lm/W ¹

LED

4000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 94 , R _r : 87 , R _{t(1-15)} : 90
MR 0.86
MDER 0.78

Optical

flood
beam angle 31°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical


DALI-2
48 V
fixture 3.3 W
optical inset 2.6 W
PC3
1 DALI Addr.

Physical

diameter 16 mm
height 600 mm
1500 mm


¹ OPTICAL INSET: incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Light distribution



flood 31°		
h (m)	E0° (lx)	ø (m)
1	731	0.56
2	183	1.12
3	81	1.67
4	46	2.23
5	29	2.79

Product drawing



Installation instructions



Lighting calculator



TILA 16 suspended

MOVE IT 10

030-6610636F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

