

TILA 16 suspended

MOVE IT 10

030-6610538M



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

jet black , RAL9005 ¹

IP20

150 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.6

MDER 0.55

Optical

medium

beam angle 23°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

inset 3.3 W

240 mA

PC3

system 45 lm/W³

1 DALI Addr.

Physical


diameter 16 mm

height 600 mm

1500 mm

Decorative pendant light inset made of aluminium; surface jet black powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 23° beam; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	717	0.41
2	179	0.81
3	80	1.22
4	45	1.62
5	29	2.03

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

