

TILA 16 adjustable

MOVE IT 10

030-6500536F



Project / Type _____


Notes _____

Count / Date _____



Decorative spotlight inset made of aluminium; surface lacquered in brushed aluminium; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 31° beam; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



flood 31°			
h (m)	E0° (lx)	ø (m)	
1	731	0.56	
2	183	1.12	
3	81	1.67	
4	46	2.23	
5	29	2.79	

Product drawing



General

Ceiling / Wall , Track _____

tilt max 135° _____

rotation 365° _____

brushed aluminium _____

IP20 _____

220 lm _____

optical inset 83 lm/W¹ _____

LED

3000 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_r: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.6 _____

MDER 0.55 _____

Optical

flood _____

beam angle 31° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 3.3 W _____

optical inset 2.6 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 16 mm _____

height 80 mm _____

¹ OPTICAL INSET: incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Installation instructions

