

TILA 32 adjustable

MOVE IT 10

030-6560636F



Project / Type _____


Notes _____

Count / Date _____



Decorative spotlight inset made of aluminium; surface lacquered in brushed aluminium; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 34° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2760	0.61
2	690	1.21
3	310	1.82
4	170	2.42
5	110	3.03

Product drawing



General

Ceiling / Wall , Track _____

tilt max 135° _____

rotation 365° _____

brushed aluminium _____

IP20 _____

846 lm _____

optical inset 97 lm/W¹ _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 , R_r: 90 , R₍₁₋₁₅₎: 89 _____

MR 0.81 _____

MDER 0.74 _____

Optical

flood _____

beam angle 34° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 9.7 W _____

optical inset 8.8 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 32 mm _____

height 120 mm _____

¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Installation instructions

