

GIRA downlight

MOVE IT 10

030-6410537F



Project / Type

Notes

Count / Date



General

Ceiling , Track
 rotation 360°
 traffic white , RAL9016 ¹
 IP20
 1160 lm

LED

3000 K
 CRI ≥ 90
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 98 , R_r: 91 , R₍₁₋₁₅₎: 89
 MR 0.6
 MDER 0.55

Optical

flood
 beam angle 34°

Electrical


DALI-2
 18.2 W
 PC3
 64 lm/W
 1 DALI Addr.

Physical

length 217 mm
 width 19 mm
 height 19 mm

Linear light inset made of aluminium; surface traffic white powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 34° beam; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	3190	0.60
2	800	1.20
3	350	1.81
4	200	2.41
5	130	3.01

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

