

# INDIRECT

MOVE IT 10  
030-6370538M



Project / Type

Notes

Count / Date



Linear light inset made of plastic; light inset can be installed and moved without tools by means of clip mount; flush with profile system; power supplied via MOVE IT system track profile; rear supply by means of Feeder; hot plug protection; fitted with single LED light points; with indirect light component for additional accentuation of the ceiling or wall; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

UGR

$\leq 10$

cd/m<sup>2</sup>

$\leq 1500$

CRI

$\geq 90$

1ADDR

### General

Ceiling / Wall , Track

IP20

2280 lm

### LED

3000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Optical

medium

### Electrical

DALI-2

32 W

PC3 48V

71 lm/W

1 DALI Addr.


### Physical

length 2000 mm


width 11 mm

height 10 mm

### Light distribution



### Product drawing



### Installation instructions

