

MOVE IT 10 track round curve

suspended
030-143103P



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

white , RAL9016/RAL9005 ¹ _____

Inner colour black _____

IP20 _____

Electrical

DALI-2 _____

PC3 48V _____

Physical

width 29 mm _____

height 26 mm _____

centerline radius 300 mm _____

segment 90° _____


¹ RAL code

Installation instructions



Thin extruded aluminium profile with 26 mm height and 10 mm width groove; tubular design; CURVE channel 90°; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; surface white; powder coated / anodised; with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of PASS THROUGH connector (as an accessory); light insets can be installed and moved without tools by means of clip mount; degree of protection IP20; PC3 48V; accessories are listed separately;

Product drawing



[030-143103P] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com