



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



General

Wall , Surface \_\_\_\_\_

anodised aluminium \_\_\_\_\_

IP20 \_\_\_\_\_

indirect 7460 lm \_\_\_\_\_

direct 7460 lm \_\_\_\_\_

total 14920 lm \_\_\_\_\_

14900 lm/m \_\_\_\_\_

LED

4000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 98 , R<sub>r</sub>: 90 , R<sub>t(1-5)</sub>: 88 \_\_\_\_\_

MR 0.76 \_\_\_\_\_

MDER 0.69 \_\_\_\_\_

Optical

Linear Prismatic \_\_\_\_\_

asymmetric \_\_\_\_\_

PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

Luminaire housing, mounting channel and front cover from extruded aluminium profile; angular design; no visible screws; surface anodised aluminium; suitable for wall mounting; equipped with two light insets made of aluminium, powder coated; direct/indirect illumination characteristic; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; direct/indirect light component separate controllable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2 \_\_\_\_\_

220-240 V \_\_\_\_\_

system 123 W \_\_\_\_\_

system 121 lm/W<sup>2</sup> \_\_\_\_\_

PC1 \_\_\_\_\_

2 DALI Addr. \_\_\_\_\_

123 W/m \_\_\_\_\_

Physical

length 1013 mm \_\_\_\_\_


width 160 mm \_\_\_\_\_

height 70 mm \_\_\_\_\_


1.7 kg \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



Product drawing



Installation instructions

