

MOVE IN 45 square

trim

063-8421516V 063-8842118 002-90726



Project / Type
Notes
Count / Date



General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set jet black
IP20
346 lm

LED

3000 K
CRI \geq 90
L85 / 50000 h
initial MacAdam \leq 2 SDCM
R _g : 98 , R _f : 91 , R _{f(1-15)} : 89
MR 0.6
MDER 0.55

Optical

super spot
beam angle 8°
PstLM \leq 1.0 ¹
SVM \leq 0.4 ¹

Electrical

non DIM
9.2 W
inset 6.9 W
11 Vf
600 mA
PC2 220-240V
38 lm/W
inset 50 lm/W

Physical

trim
diameter 78 mm
height 105 mm
0.37 kg

Cutout

diameter 70 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 180 mm

¹ Value of containing product at full load (undimmed)

Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



Installation instructions



Lighting calculator



[063-8421516V 063-8842118 002-90726] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.11.2024