

MOVE IN 45 square

trim

063-8421516M 063-8842118 002-90724



Project / Type

Notes

Count / Date



220-240V

X-PERT

UGR

≤ 10

CRI

≥ 90

X-PERT

General

Ceiling , Semi-Recessed

brushed aluminium

Mounting set jet black

IP20

1270 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.59

MDER 0.53

Optical

medium

beam angle 24°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

non DIM

15.9 W

inset 13.5 W

36 Vf

400 mA

PC2 220-240V

80 lm/W

Physical

trim

diameter 78 mm

height 105 mm

0.41 kg

Cutout


diameter 70 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 180 mm



Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	6120	0.43
2	1530	0.86
3	680	1.30
4	380	1.73
5	240	2.16

Product drawing



¹ Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator

