

MOVE IN 45 square

trim

063-8421514M 063-8842118 002-90724



| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |



General

| |
|------------------------------|
| Ceiling , Semi-Recessed |
| chrome |
| Mounting set jet black |
| IP20 |
| 1270 lm |
| fixture 95 lm/W ¹ |

LED

| |
|---|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 100 , R _f : 91 , R _{f(1-5)} : 88 |
| MR 0.59 |
| MDER 0.53 |

Optical

| |
|--------------------------|
| medium |
| beam angle 24° |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|----------------|
| non DIM |
| 220-240 V |
| system 15.9 W |
| fixture 13.5 W |
| 36 Vf |
| 400 mA |
| PC2 |

Physical

| |
|----------------|
| trim |
| diameter 78 mm |
| height 105 mm |
| 0.41 kg |

Cutout

| |
|------------------------------|
| diameter 70 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 180 mm |

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
² Value of containing product at full load (undimmed)

Light distribution



medium 24°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 6120 | 0.43 |
| 2 | 1530 | 0.86 |
| 3 | 680 | 1.30 |
| 4 | 380 | 1.73 |
| 5 | 240 | 2.16 |

Product drawing



Installation instructions



Lighting calculator

