

MOVE IN 45 flex round

trimless

063-8221516V 063-8812117 002-90726



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed
 tilt max 90°
 rotation 360°
 brushed aluminium
 Mounting set traffic white
 IP20
 346 lm

LED

3000 K
 CRI ≥ 90
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 98 , R_r: 91 , R₍₁₋₁₅₎: 89
 MR 0.6
 MDER 0.55

Optical

super spot
 beam angle 8°
 P_{stLM} ≤ 1.0¹
 SVM ≤ 0.4¹

Electrical

non DIM
 9.2 W
 inset 6.9 W
 11 Vf
 600 mA
 PC2 220-240V
 38 lm/W

Physical

trimless
 diameter 75 mm
 height 106 mm
 0.6 kg


Cutout

diameter 65 mm
 min. ceiling thickness 9 mm
 max. ceiling thickness 25 mm
 recessed depth 200 mm

¹ Value of containing product at full load (undimmed)

Round spotlight element in aluminium; surface brushed aluminium; installation without tools in mounting set due to patented ball catch system; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 9-25 mm; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 8° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



Installation instructions



Lighting calculator

