

MOVE IN 32 flex round

trim

063-8211516S 063-8821118 002-90743



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Semi-Recessed
 tilt max 90°
 rotation 360°
 brushed aluminium
 Mounting set jet black
 IP20
 800 lm
 fixture 91 lm/W¹

LED

3000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 100 , R_f: 91 , R_{1-15}: 88
 MR 0.59
 MDER 0.53

Optical

spot
 beam angle 18°
 PstLM ≤ 1.0²
 SVM ≤ 0.4²

Electrical

DALI-2
 220-240 V
 system 11.7 W
 fixture 8.7 W
 36 Vf
 250 mA
 PC2
 1 DALI Addr.

Physical

trim
 diameter 65 mm
 height 93 mm
 0.46 kg

Cutout


diameter 54 mm
 min. ceiling thickness 2 mm
 max. ceiling thickness 25 mm
 recessed depth 140 mm

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

² Value of containing product at full load (undimmed)

Round spotlight element in aluminium; surface brushed aluminium; installation without tools in mounting set due to patented ball catch system; recessed light with trim jet black; suitable for ceiling thickness of 2-25 mm; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 18° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	6060	0.32
2	1510	0.63
3	670	0.95
4	380	1.27
5	240	1.58

Product drawing



MOVE IN 32 flex round

trim

063-8211516S 063-8821118 002-90743



Project / Type

Notes

Count / Date

**Installation
instructions**



**Lighting
calculator**

