

MOVE IN 32 flex round

trimless

063-8211516F 063-881117 002-90742



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

brushed aluminium

IP20

795 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f1-15}: 88

MR 0.59

MDER 0.53

Optical

flood

beam angle 34°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

non DIM

system 11.7 W

inset 8.7 W

36 Vf

250 mA

PC2 220-240V

system 68 lm/W²

inset 91 lm/W³

Physical

trimless

diameter 63 mm

height 92 mm

0.51 kg

Cutout

diameter 54 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 110 mm

¹ Value of containing product at full load (undimmed)

² incl. optical losses and the efficiency of the operating device (converter)

³ incl. optical losses

Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2590	0.61
2	650	1.21
3	290	1.82
4	160	2.42
5	100	3.03

Product drawing



Installation instructions



Lighting calculator

