

MOVE IN 45 flex round

trim

063-8221416M 063-8822118 002-90724



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

brushed aluminium

Mounting set jet black

IP20

1200 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optical

medium

beam angle 24°

P_{stLM} ≤ 1.0¹

SVM ≤ 0.4¹

Electrical

non DIM

system 15.9 W

inset 13.5 W

36 Vf

400 mA

PC2 220-240V

system 75 lm/W²

inset 89 lm/W³

Physical

trim

diameter 77 mm

height 107 mm

0.43 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

¹ Value of containing product at full load (undimmed)

² incl. optical losses and the efficiency of the operating device (converter)

³ incl. optical losses

Light distribution



h (m)	E0° (lx)	ø (m)
1	5780	0.43
2	1440	0.86
3	640	1.30
4	360	1.73
5	230	2.16

Product drawing



Installation instructions



Lighting calculator

