

MOVE IN 45 flex round

trim

063-8221416M 063-8822117 002-90724



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

tilt max 90°

rotation 360°

brushed aluminium

Mounting set traffic white

IP20

1200 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optical

medium

beam angle 24°

P_{stLM} ≤ 1.0¹

SVM ≤ 0.4¹

Electrical

non DIM

system 15.9 W

inset 13.5 W

36 Vf

400 mA

PC2 220-240V

system 75 lm/W²

inset 89 lm/W³

Physical

trim

diameter 77 mm

height 107 mm

0.44 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

¹ Value of containing product at full load (undimmed)

² incl. optical losses and the efficiency of the operating device (converter)

³ incl. optical losses

Light distribution



| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 5780 | 0.43 |
| 2 | 1440 | 0.86 |
| 3 | 640 | 1.30 |
| 4 | 360 | 1.73 |
| 5 | 230 | 2.16 |

Product drawing



Installation instructions



Lighting calculator

