

MOVE IN 32 flex round

trim

063-8211416M 063-8821117 002-90743



Project / Type

Notes

Count / Date




General
Ceiling , Semi-Recessed
tilt max 90°
rotation 360°
brushed aluminium
Mounting set traffic white
IP20
786 lm

LED
2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _r : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Optical
medium
beam angle 24°
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Electrical
DALI-2
11.6 W
inset 8.7 W
36 Vf
250 mA
PC2 220-240V
68 lm/W
1 DALI Addr.

Light distribution



medium 24°		
h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

Product drawing



Physical
trim
diameter 65 mm
height 93 mm
0.45 kg

Cutout
diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 140 mm

¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

