

MOVE IN 45 round

trim

063-8121517V 063-8822117 002-90726



Project / Type
Notes
Count / Date



General

Ceiling , Semi-Recessed
white , RAL 9016 ¹
Mounting set traffic white
IP20
346 lm
fixture 50 lm/W ²

LED

3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 98 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.6
MDER 0.55

Optical

super spot
beam angle 8°
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³

Electrical

non DIM
220-240 V
system 9.2 W
fixture 6.9 W
11 Vf
600 mA
PC2

Physical

trim
diameter 77 mm
height 107 mm
0.42 kg

Cutout

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 200 mm

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



Installation instructions



Lighting calculator

