

MOVE IN 45 round

trim

063-8121516V 063-8822117 002-90726



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set traffic white
IP20
346 lm

LED

3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 98 , R_f: 91 , R_{f(1-15)}: 89
MR 0.6
MDER 0.55

Optical

super spot
beam angle 8°
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Electrical

non DIM
system 9.2 W
inset 6.9 W
11 Vf
600 mA
PC2 220-240V
system 38 lm/W²
inset 50 lm/W³


Physical

trim
diameter 77 mm
height 107 mm
0.42 kg

Cutout

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 200 mm

Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Product drawing



¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)
³ incl. optical losses

Installation instructions



Lighting calculator

