

MOVE IN 45 round

trim

063-8121414S 063-8822117 002-90722



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

chrome

Mounting set traffic white

IP20

1040 lm

fixture 81 lm/W¹

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.53

MDER 0.48

Optical

spot

beam angle 12°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

220-240 V

system 15.0 W

fixture 12.7 W

37 Vf

350 mA

PC2

Physical

trim

diameter 77 mm

height 107 mm

0.62 kg

Cutout

diameter 65 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
² Value of containing product at full load (undimmed)


Light distribution



spot 12°

h (m)	E0° (lx)	ø (m)
1	13200	0.21
2	3300	0.42
3	1500	0.63
4	800	0.84
5	500	1.06

Product drawing



Installation instructions



Lighting calculator

