

# MOVE IN 32 round

trim

063-8111416S 063-8821117 002-90742



Project / Type
Notes
Count / Date



## General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set traffic white
IP20
754 lm
fixture 86 lm/W <sup>1</sup>

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Optical

spot
beam angle 18°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM
220-240 V
system 11.6 W
fixture 8.7 W
36 Vf
250 mA
PC2

## Physical

trim
diameter 65 mm
height 93 mm
0.33 kg

## Cutout

diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

<sup>1</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	5710	0.32
2	1430	0.63
3	630	0.95
4	360	1.27
5	230	1.58

## Product drawing



## Installation instructions



## Lighting calculator

