

MOVE IN 32 round

trim

063-8111416F 063-8821117 002-90743



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|----------------------------|
| Ceiling , Semi-Recessed |
| brushed aluminium |
| Mounting set traffic white |
| IP20 |
| 750 lm |

LED

| |
|---|
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.53 |
| MDER 0.48 |

Optical

| |
|--------------------------|
| flood |
| beam angle 34° |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Electrical

| |
|--------------|
| DALI-2 |
| 11.6 W |
| inset 8.7 W |
| 36 Vf |
| 250 mA |
| PC2 220-240V |
| 65 lm/W |
| 1 DALI Addr. |

Physical


| |
|----------------|
| trim |
| diameter 65 mm |
| height 93 mm |
| 0.3 kg |

Cutout

| |
|------------------------------|
| diameter 54 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 140 mm |

¹ Value of containing product at full load (undimmed)

Light distribution



flood 34°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 2450 | 0.61 |
| 2 | 610 | 1.21 |
| 3 | 270 | 1.82 |
| 4 | 150 | 2.42 |
| 5 | 100 | 3.03 |

Product drawing



Installation instructions



Lighting calculator

