

# MOVE IN 32 round

trim

063-8111516S 063-8821118 002-90742



Project / Type
Notes
Count / Date



## General

Ceiling , Semi-Recessed
brushed aluminium
Mounting set jet black
IP20
800 lm

## LED

3000 K
CRI $\geq 90$
L80 / 50000 h
initial MacAdam $\leq 2$ SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-15)</sub> : 88
MR 0.59
MDER 0.53

## Optical

spot
beam angle 18°
PstLM $\leq 1.0$ <sup>1</sup>
SVM $\leq 0.4$ <sup>1</sup>

## Electrical

non DIM
system 11.7 W
inset 8.7 W
36 Vf
250 mA
PC2 220-240V
system 68 lm/W <sup>2</sup>
inset 91 lm/W <sup>3</sup>

## Physical

trim
diameter 65 mm
height 93 mm
0.32 kg

## Cutout

diameter 54 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>3</sup> incl. optical losses

## Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	6060	0.32
2	1510	0.63
3	670	0.95
4	380	1.27
5	240	1.58

## Product drawing



## Installation instructions



## Lighting calculator

