

FLEXTRACK

MOVE IT 25
050-750401G



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

rotation 360°

gold , gold dust/RAL9005 ¹

Inner colour black

IP20

LED

3000 K

Electrical

non DIM

PC3 48V

Physical

length 1210 mm

width 31 mm

height 31 mm

1.1 kg

¹ RAL code

Thin extruded aluminium profile with 31mm height and 28mm width groove; surface gold powder coated; with integrated power rail profile for supply voltage feed; for installation in two MOVE IT 25 profiles; profile can be installed and moved without tools by means of magnetic holders+locking; mount 360° rotatable and freely slidable on one end; light insets can be installed and moved without tools by means of magnetic holders+locking; degree of protection IP20; PC3 48V;

Product drawing



Installation instructions



[‘050-750401G’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com