

# SQUADRO double-sided wallwasher

track  
149-2220018B



Project / Type

Notes

Count / Date



General
Ceiling , Track
tilt min -10°
tilt max 20°
rotation 350°
black , RAL9005 <sup>1</sup>
IP20
4910 <sup>2</sup> , 4920 <sup>3</sup> , 9830 <sup>4</sup> lm

LED
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 98 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 93
MR 0.54
MDER 0.49


Optical
shelf / wall floor washer
PstLM ≤ 1.0 <sup>5</sup>
SVM ≤ 0.4 <sup>5</sup>

Tracked spotlight in die cast aluminium with 2x2-lamp design; surface black powder coated; converter integrated into spotlight head; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; Aisle spotlight 1x shelf / 1x wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable +20° to -10°); 350° rotatable; degree of protection IP20; IP 40 protection glass available as an accessory; accessories are listed separately; PC2 220-240V; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; including attachment for linear alignment of the spotlights; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Electrical
non DIM
system 36 <sup>2</sup> -72 <sup>3</sup> W
PC2 220-240V
system 136 <sup>2</sup> , 137 <sup>3</sup> , 137 <sup>4</sup> lm/W <sup>6</sup>

Physical
length 140 mm
width 150 mm
height 76 mm

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> single sided shelf floor <sup>3</sup> single sided wall floor  
<sup>4</sup> double-sided  
<sup>5</sup> Value of containing product at full load (undimmed)  
<sup>6</sup> incl. optical losses and the efficiency of the operating device (converter)

### Installation instructions

