

# BETO sensor direct / indirect power

free standing T-shape  
074-69555SXB



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 x 42 mm); square downpipe; pedestal with recess for table base (T-shape); surface special colours powder coated; direct/indirect illumination characteristic; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; Reflector dark chrome; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; UGR ≤ 10; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. Loxone Air module for easy integration into the Loxone home and building automation system; luminaire with integrated infrared presence and brightness sensor (ESSENTIAL sensor); luminaire with integrated miniature push-button; presence sensor detection range ø4,5m on the floor; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Floor , Standing \_\_\_\_\_

special colours \_\_\_\_\_

Reflector dark chrome \_\_\_\_\_

black \_\_\_\_\_

IP20 \_\_\_\_\_

indirect 6630 lm \_\_\_\_\_

direct 1490 lm \_\_\_\_\_

total 8120 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

MR 0.56 \_\_\_\_\_

MDER 0.51 \_\_\_\_\_

## Optical

Reflector \_\_\_\_\_

asymmetric \_\_\_\_\_

UGR ≤ 10 \_\_\_\_\_

PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

## Electrical

Loxone Air incl. ESSENTIAL sensor \_\_\_\_\_

220-240 V \_\_\_\_\_

system 66 W \_\_\_\_\_

system 123 lm/W<sup>2</sup> \_\_\_\_\_

PC1 \_\_\_\_\_

## Physical

T-shape \_\_\_\_\_

length 1055 mm \_\_\_\_\_

width 42 mm \_\_\_\_\_

height 2100 mm \_\_\_\_\_

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

