

NOBA 60 suspended

MOVE IT 10

030-6920539



Project / Type	
Notes	
Count / Date	



General

Ceiling , Track Suspended
rose gold
IP20
922 lm
optical inset 126 lm/W ¹

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Optical

wide flood
beam angle 67°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrical

DALI-2
48 V
fixture 8.1 W
fixture 114 lm/W ³
optical inset 7.3 W
PC3
1 DALI Addr.

Physical

diameter 60 mm
height 60 mm
1500 mm


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	876	1.31
2	219	2.63
3	97	3.94
4	55	5.26
5	35	6.57

Product drawing



¹ OPTICAL INSET: incl. consideration of optical losses
² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

