

# NOBA 60 suspended

MOVE IT 10

030-6920435




Project / Type	
Notes	
Count / Date	



Decorative pendant light inset made of aluminium; surface anodised gun metal; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	826	1.31
2	207	2.63
3	92	3.94
4	52	5.26
5	33	6.57

## Product drawing



## General

Ceiling , Track Suspended	
gun metal	
IP20	
869 lm	

## LED

2700 K	
CRI $\geq 90$	
L80 / 50000 h	
initial MacAdam $\leq 2$ SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89	
MR 0.53	
MDER 0.48	

## Optical

wide flood	
beam angle 67°	
PstLM $\leq 1.0$ <sup>1</sup>	
SVM $\leq 0.4$ <sup>1</sup>	

## Electrical

DALI-2	
system 8.1 W	
PC3	
system 107 lm/W <sup>2</sup>	
1 DALI Addr.	

## Physical

diameter 60 mm	
height 60 mm	
1500 mm	

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

## Installation instructions



## Lighting calculator

