

NOBA 60 suspended

MOVE IT 10

030-6920435



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

gun metal _____

IP20 _____

869 lm _____

optical inset 119 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

wide flood _____

beam angle 67° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 8.1 W _____

optical inset 7.3 W _____

PC3 _____

1 DALI Addr. _____

Physical

diameter 60 mm _____


height 60 mm _____

1500 mm _____

¹ OPTICAL INSET: incl. consideration of optical losses


² Value of containing product at full load (undimmed)

Light distribution



wide flood 67°			
h (m)	E0° (lx)	ø (m)	
1	826	1.31	
2	207	2.63	
3	92	3.94	
4	52	5.26	
5	33	6.57	

Product drawing



Installation instructions

Lighting calculator

