

NOBA 40 suspended

MOVE IT 10

030-6900535



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface anodised gun metal; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 69°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling , Track Suspended

gun metal

IP20

405 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optical

wide flood

beam angle 69°

Electrical

DALI-2

3.5 W

PC3

116 lm/W

1 DALI Addr.

Physical

diameter 40 mm

height 40 mm

1500 mm


Light distribution



wide flood 69°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 358 | 1.37 |
| 2 | 89 | 2.74 |
| 3 | 40 | 4.12 |
| 4 | 22 | 5.49 |
| 5 | 14 | 6.86 |

Product drawing



Installation instructions



Lighting calculator

