

NOBA 60 adjustable

MOVE IT 10

030-6820539



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 365°

rose gold

IP20

922 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Decorative spotlight inset made of aluminium; surface anodised rose gold; 365° rotatable and 90° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Electrical

DALI-2


system 8.1 W

PC3

system 114 lm/W²

1 DALI Addr.


Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	876	1.31
2	219	2.63
3	97	3.94
4	55	5.26
5	35	6.57

Product drawing



Physical

diameter 60 mm

height 60 mm

¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions

