

# NOBA 60 adjustable

MOVE IT 10

030-6820433



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling / Wall , Track \_\_\_\_\_

tilt max 90° \_\_\_\_\_

rotation 365° \_\_\_\_\_

brushed brass \_\_\_\_\_

IP20 \_\_\_\_\_

851 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optical

wide flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

8.1 W \_\_\_\_\_

PC3 \_\_\_\_\_

105 lm/W \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

## Physical

diameter 60 mm \_\_\_\_\_

height 60 mm \_\_\_\_\_

## Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	809	1.31
2	202	2.63
3	90	3.94
4	51	5.26
5	32	6.57

## Product drawing



## Installation instructions

