

NOBA 40 adjustable

MOVE IT 10

030-6800635



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling / Wall , Track _____
 tilt max 90° _____
 rotation 365° _____
 gun metal _____
 IP20 _____
 429 lm _____
 optical inset 136 lm/W¹ _____

LED

4000 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 2 SDCM _____
 R_g: 97 , R_r: 90 , R₍₁₋₁₅₎: 89 _____
 MR 0.81 _____
 MDER 0.74 _____

Optical

wide flood _____
 beam angle 69° _____
 P_{stLM} ≤ 1.0² _____
 SVM ≤ 0.4² _____

Electrical

DALI-2 _____
 48 V _____
 fixture 3.5 W _____
 fixture 123 lm/W³ _____
 optical inset 3.2 W _____
 PC3 _____
 1 DALI Addr. _____

Physical

diameter 40 mm _____
 height 40 mm _____


¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Decorative spotlight inset made of aluminium; surface anodised gun metal; 365° rotatable and 90° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 69°; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



wide flood 69°

h (m)	EO° (lx)	ø (m)
1	379	1.37
2	95	2.74
3	42	4.12
4	24	5.49
5	15	6.86

Product drawing



Installation instructions

