

# MINO 40 reflector

ceiling / suspended system

042-0113137B 042-1004018



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Suspended
black , RAL 9005 <sup>1</sup>
Reflector dark chrome
IP20
3650 lm
2430 lm/m

### LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 92 , R <sub>(1-15)</sub> : 90
MR 0.81
MDER 0.74

### Optical

Reflector
symmetric
UGR < 19 , ≥65° <1500 cd/m <sup>2</sup>
P <sub>stLM</sub> ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


### Electrical

DALI-2
220-240 V
system 36 W
system 101 lm/W <sup>3</sup>
PC1
1 DALI Addr.
24 W/m

### Physical

length 1500 mm
width 40 mm
height 65 mm
5.5 kg

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

