


MINO 40 reflector

ceiling / suspended system

042-0112037B 042-100201W



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|---|
| Ceiling , Suspended |
| RAL Traffic white , RAL 9016 ¹ |
| Reflector dark chrome |
| 2250 lm/m |
| IP20 |
| 2250 lm |

LED

| |
|--|
| 3000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89 |
| MR 0.61 |
| MDER 0.55 |

Optical

| |
|---|
| Reflector |
| symmetric |
| UGR < 19 , ≥65° <1500 cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical


| |
|--------------|
| DALI-2 |
| 24.4 W |
| PC1 220-240V |
| 92 lm/W |
| 1 DALI Addr. |
| 24 W/m |

Physical

| |
|----------------|
| length 1000 mm |
| width 40 mm |
| height 65 mm |
| 5.5 kg |

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

